



FIFA Preferred Artificial Turf Shock Pad Laminated Fast Installation 60kg/m3

Our Product Introduction

for more products please visit us on shockpadunderlay.com

Basic Information

- Place of Origin: China
- Brand Name: TAIHUI
- Certification: SGS/LABOSPORT/SPORTSLABS
- Model Number: Shock pads
- Minimum Order Quantity: 1,000 sqms
- Price: As per discussion
- Packaging Details: In rolls
- Delivery Time: One week
- Payment Terms: T/T
- Supply Ability: 500,000 sqms per month



Product Specification

- Density: 60kg/m3
- Feature: Shock Absorbing And Providing Safety
- Installation Method: Roll Out
- Packing: In Rolls
- Service Year: More Than 20 Years
- Size: Customizable
- Standard Thickness: 10mm, 12mm, 15mm, 20mm And More
- Temperature Resistance: -40°C To 70°C
- Transport: 5000 Sqms In 40' Feet Container
- Usage: Soccer Rugby Baseball Hockey Field
- Water Absorption: Close Celled Doesn't Absorb Water
- Weight: 700 G/m2
- Width: 1m/1.25m/1.5m/1.8m/2.0m
- UV Resistance: >6,000 Hours
- Highlight: FIFA Preferred Artificial Turf Shock Pad,



More Images



Product Description

FIFA Preferred Artificial Turf Shock Pads Laminated Fast Installation for Soccer Rugby Baseball Hockey Field

Artificial Turf System

1. Proposal without infill:

Ground base + 10 mm TAIHUI shock pad + 35~40 mm artificial turf

Scope of application: Sites for minors using (mainly for primary and secondary school sites).

2. Standard proposal:

Ground base + 10 mm TAIHUI shock pad + 45~55 mm artificial turf + 25~35 kg silica sand + 5 kg TAIHUI Eco-friendly infill

Scope of application: Sites for adult (mainly for University sites), five-person or seven-person sites for operating

3. Proposal of FIFA QUALITY PRO:

Ground base + 10 mm TAIHUI shock pad + 50 mm artificial turf + 25~35 kg silica sand + 6 kg TAIHUI Eco-friendly infill.

Applicable scope: Certified professional events sites.

Our shock pad enjoys advantages as below:

| | |
|--------------|---------------------------------------------------------------------------------------------------------------------|
| Structure | Made of three layers with film on the backing to enhance the tensile strength and UV. |
| Material | Environmentally friendly resin, no odor. |
| Appearance | Black and blue or customized color |
| Character | Light in weight, closed celled foam without absorbing water. |
| Spec | Selectable density and thickness suit for all pitch standard. |
| Installation | Easy and good-looking installation. |
| Test report | Labosport & SGS & Sportslabs |
| Function | Reduce the overall cost of the artificial grass system, enhance the performance, extend the life span of the system |

Product Specifications




| | |
|------------------|------------------------------------|
| Model: | T2504B/2506K |
| Thickness: | 8-30 mm |
| Material: | New environmental friendly PE foam |
| Density: | 50 kg/m3 |
| Color: | Black and blue or other colors |
| Features: | closed cell foam, 3-layers. |
| Production size: | W1.5m * L50m or tailored length |
| Production time: | Normally within 1 week |
| Package: | Recyclable PE bag |

Product Advantages

Material—The perfect combination of new environmental protection resin and rubber foam, rubber has a strong tensile strength and softness, which ensure the strong elasticity and softness brings sense of comfort at the same time. The UV resistant film brings the long service life for the shock pad which is more environmentally friendly, no odor.

Tensile strength—Three-layer structure and characteristics of rubber makes the shock pad with the strong tensile strength, which will protect the product from deformation and damage during the installation. Tensile strength of one-time forming process product is poor.

Cost—Our shock pad can be installed directly on the water stabilized base, and then covered by artificial turf, which helps to save the cost of concrete or asphalt base. Artificial grass pile height 40 mm filled with quartz sand and granules, whose overall cost is lower than the traditional grass pile 50mm without any infill.

| Test Content | Tested by |
|------------------------------|--------------------------------------------------------------------------------------|
| Performance Test |  |
| Compression Deformation Test | |
| Water Permeability Test |  |
| Environmental Test |  |

Scope of Application



Our Workshop



Our Installation on Site





Trust we will support you by excellent quality and friendly price. Our products will make your artificial turf pitch fantastic!

Welcome for any inquiry.



CHANGZHOU TAIHUI SPORTS MATERIAL CO.,LTD



13915088459



grace@taihuisports.com



shockpadunderlay.com

Building 3A-602, R&D Hub, Science&education Tower,Wujin District, China.